

Pacejet

Coding and Marking Solution



PACEJET - H1506UHS WHITE

100KH_z High Speed + Small Character Inkjet Printer

Advanced Capabilities

- German Latest Stirring System (for trouble free pigmented ink operation, dominant & uniform print quality)
- 48dots 8 lines of high-resolution print with speeds up to 1,476 fpm (800 mpm), 5x5 one line.
- Advanced connectivity makes integration simpler (RS232, USB, RJ45, Wi-fi, Ethernet)

Simple to maintain

- No ink core, no ink module, one main filter only.
- 2000 – 6000 hrs depend on operational environment.



Pacejet
Coding and Marking Solution

Pacejet

Coding and Marking Solution

Line Speed Capability

- 1 line 5x5 @ 800 mpm
- 1 line 7x5 @ 650 mpm
- 2 lines 7x5 @ 450 mpm
- 3 lines 7x5 @ 300 mpm
- 4 lines 7x5 @ 60 mpm

Font Matrix Configuration

- Single-line : 5x5, 7x5, 9x7, 11x7, 15x11, 23x15, 32x24
- Twin-line : 5x5, 7x5, 9x7, 11x7, 15x11, 23x15
- Tri-line : 5x5, 7x5, 9x7, 11x7, 15x11
- Quad-line : 5x5, 7x5, 9x7, 11x7

Linear Bar Codes

- Code39, Code128, EAN128, EAN-8, EAN-13, UPC A&E, QR code, DataMatrix

Character Height

- Selectable from 0.1 cm (0.04") to 2 cm (0.8"), depending on font

Throw Distance

- Optimal : 15 mm (0.6")
- Range : 0.5 mm (0.2") to 50 mm (2")

Display & Key-in

- 10" 800X640 Full HD touch screen
- WYSIWYG on-screen message editing, Linux smart OS with iPhone-level user experience



Nozzle Specifications

- 40U 50U 60U 70U 80U

Custom Logo/Graphics

- Can be created by user on build-in logo editor on printer, or on PC by Microsoft Paint.

Character Sets

- English, Chinese, Arabic, Farsi, Latin, etc

Language and Interface Options

- English, Chinese(S+T), Arabic, Vietnamese, Thai, Farsi, French, German, Korean, Spanish, etc

Message Storage

- 1000 complex messages.

Fluid Containers

- 1500ml refillable reservoir (Ink/Solvent)

Temperature/Humidity Range

- 5°C (41°F) to 45°C (113°F)
- 0% to 90% RH non-condensing

Electrical Requirements

- Power supply 100-120/ 200-240 VAC, 50/60Hz, 120W

Net Weight

- Unpacked and dry : 27 kg (59.5 lbs)

Environmental Protection

- 316 stainless steel, IP55 standard, no plant air required

Print Head Umbilical

- 3.5 meters standard, up to 5 meters

Options

Remote control software kit (Win10), RJ45 or Wi-Fi
Food grade version
Wide range of accessories (Sensors/Encoders/etc)

Ink Color

- White, Yellow, Green, Blue, Pink, Red, Brown

CODING SAMPLES



CABLE 160 MM (INDIA) 1234 150 MTR

123 CABLE HITECH CBLE @ 251

MTB Coding PROJECT WIRE

HITECH	INKJET	PUT	LTD	HITECH	INKJET
PAGEJET	1234@123			PAGEJET	1234@1
RAJDHANI	CABLE	1100	V	RAJDHANI	CABLE

© BONY MEI-0130 © BONY MEI-01

E203950 c 7/1/55 WOER RSFR-H TUBE 125° C VW-1 H (88)

HITECH INKJET PVT LTD PAGEJET

Pacejet

Coding and Marking Solution



HITECH INKJET PVT LTD.

📍 Corporate office:- C-40, TEN TOWER, FIRST FLOOR, SECTOR - 15, VASUNDHARA, GHAZIABAD, 201012

📍 Works:- 12/28, Site-IV, Pioneer Complex UPSIDC, Sahibabad Industrial Area, Ghaziabad, UP- 201010

☎ 0120-4107373, +91 9999683644

+91 8448982802, +91 8448982811

✉ Info@hitechinkjet.com

✉ hitech.inkjet@gmail.com

📘 www.facebook.com/hitechinkjet

🌐 www.hitechinkjet.com